

Version 2.0.1 - EN

22-07-2014

User manual DVB-T tuner

Art. Number:

DVB-LOGIC DVB-LOGIC-CO





Content

1: IMPORTANT INFORMATION	2
2: INBOUW- & VEILIGHEIDS INSTURCTIES	3
3: SCOPE OF DELIVERY	3
4: PRODUCT FEATURES	4
5: OVERVIEW	5
6: REQUIREMENTS	6
7: INSTALLATIE	7
8: FAQ	21
9: WARRANTY	23
10: TECHNICAL DATA	23
11: TECHNICAL SUPPORT	23





1: IMPORTANT INFORMATION

You have made the right choice by purchasing advanced NavInc multimedia products. We recommend to read the installation instructions carefully before starting the installation.

Installation must be done by a qualified personnel. Installation of the interface is entirely at your own risk. We accept no liability for damage to the vehicle or personal injury. If the manual is not well enforced and / or the interface is incorrectly connected, the guarantee claim as well the operating permission becomes invalid.

The guarantee claim as well the operating permission becomes invalid due to:

- *a)* The housing is opened
- b) The warranty sticker is damaged or broken
- c) The interface is damaged
- d) Capital repairs are performed
- e) Cable / connector is modified
- f) Brute force to the device

The operation of this interface may be affected by software updates from the manufacturer / dealer. In such cases, within one year of purchase, we provide a free software update for the multimedia interface. The costs for removal and de/re-installation is not included and the interface must be supplied to us.

In the supplied (service) instructions you can specify how and where the products are installed. In addition, end users are made aware of important addresses that he can consult in case of questions or problems. We advise you and the end-user to give the service record to the dealer when maintenance must be done.

Warranty must be done via a RMA request. Returns without (copy) invoice, RMA form and RMA number will not be accepted. Returns can only be sent after agreement RMA request.

General Guidelines for Maintenance:

a) For repair / maintenance end-user must always show the Service instructions to the dealer.

b) If the vehicle goes to a dealer for service, it may be necessarily that the interface module (s) must be temporarily removed due to a software update or reading failures.

c) In this case, the loop-through adapters (optional) can be used to remove easily the interface modules.

NavInc thank you for your choice and wish you lots of media fun!



2: INBOUW- & VEILIGHEIDS INSTURCTIES

Installation must be done by a qualified personnel.

Do not install this interface by yourself. For safe and reliable installation, consult a dealer having special knowledge.

- \circ Use the device only at a +12 volt vehicle electrical system. Make sure to have a proper ground.
- *The device should not be set up in direct proximity of heat sources (e. g. power amplifier).*
- Please make sure that no objects or liquids can intrude the interior of the device! (Danger of short circuit!)
- Please follow all caution advises contained in the mounting guidelines.
- Please read through all safety instructions and handling directions intently before installation and start up of the device.
- Check alway the compatibility of the interface for your car before installation. You can check the compatibility on www.navinc.nl or call NavInc for support.
- Avoid installing the unit in following places: Where it would hinder your safe driving Where it could damage the car's fitting.
- Make sure the power is fused with 7A or 10A fuses.
- Please check all the car functions after installing the interface.
- Make sure the end customer can always reset the interface. You can reset the interface to make it powerless.

C€ ===12V DC





This equipment is to be serviced by trained personnel only.



3: SCOPE OF DELIVERY

- 1. DVB-LOGIC
- 2. Kabelkit
- 3. Manual
- 4. Service instructions guide

4: PRODUCT FEATURES

- Dual DVB-T tuner
- DVB-T MPEG2 and MPEG4 compatible (HD)
- AFS* auto frequenzy switching
- USB AV-player port
- USB-devices up to 2TB (FAT32 and NTFS), supports Audio, Video and Photo files
- Support of all common Audio & Video formats (e.g MKV, MOV, MPEG-1/2/4, H.264)
- Last position memory (for Audio and Video playback)
- IR-remote conrol

*AFS - Auto Frequency Switching is a intelligent function which allow to use always the strongest signal of an selected service by scanning all other frequencies the selected service is available. All same services are merged to only one visible station. All available frequencies are handled by the system in an not visible data base.





5: OVERVIEW

Connection DVB-LOGIC

Kabelkeuren	Connection
Red	+12V Permanent
Pink	+12V Ignition power
Black	Ground
Blue	Steering input cable

Remote control operations

	Button name	Function	
1	SOURCE	No function	
2	POWER	Select power-on or stand-by	
3	СН 🔺	Select channel up or move the cursor up	
4	MENU	Enter the setup menu	
5	OK	Select the highlighted item	
6	VOL <	Select volume down or move the cursor left	
7	СН▼	Select channel down or move the cursor down	
8	EXIT	Exit the current setup	
9	1, 2, 3,0		
10	RECALL	Return to the last selected channel	
11	GREEN BUTTON	Hot key to enter Teletext pages in Teletext mode	
12	RED BUTTON	Subtitle key in normal operation mode or the hot key to enter Teletext pages in Teletext mode	
13	MUTE	Mute control	
14	DTV/RADIO	Select digital TV or digital radio	
15	PIC	No function	
16	EPG	Electronic Program Guide	
17	VOL	Select volume up or move the cursor right	
18	PREVIEW	Enter preview mode in DVB-T TV	
19	PLAY/PAUSE	Select play or pause	
20	AUDIO	Select second language and stereo audio	
21	INFO	Display digital TV system information	
22	AUTO SCAN	To scan channels automatically	
23	MANUAL	To manually select channels	
24	ENTER	To enter the selected channel number	
25	TTX	To display teletext content	
26	YELLOW BUTTON	Select page up in the EPG mode or the hot key to browse teletext pages in Teletext mode	
27	BLUE BUTTON	Select page down in the EPG mode or the hot key to browse Teletext pages in Teletext mode	





6: REQUIREMENTS

1: When you receive this package you have to check whether there's any parts not included and you have to contact us right away.

2: Get the right installation tools





7: INSTALLATIE

Attention; do not install the interface when the ignition is ON.

7.1 Installation

Remote control battery installation

Before attempting to operate your remote control, install the battery as described below.

- 1. Turn the remote control face down.
- 2. Press down on the ridged area of the battery cover and slide it off.
- 3. Slide battery in obeying the polarity.



Connection cable kit

Black	Ground
Pink	ACC
Red	+12V battery
Blue	Cable for connection of IR-control cable
(when y	you connect the blue wire with +12V you will destroy the DVB-T tuner permanently)
	NAVIGATION & MULTIMEDIA

7.2 User instructions

Main Menu

In the menu mode, you can highlight the service type, program list, preview, audio channel, program editing, program info, automatic search, manual search, and system setting to enable the related function. You can use [CH+], [CH-], [VOL+], and [VOL-] buttons to highlight the item and press [OK] button to set the setting.





DVB-T TV Mode

mode.

To enter DVB-T TV



DVB-T Radio Mode

To listen to DVB-T radio broadcasting.



<u>Movie Playback Mode</u> To enter movie playback mode and watch movie files.



Music Playback Mode To enter audio playback mode and listen to music.



<u>Photo Viewing Mode</u> To enter photo viewing mode and watch pictures.



<u>System Settings</u> To configure the device settings.

Note: Press the [HOME] key to go back to the home screen anytime. Press the [SOURCE] key to switch AV source anytime.



DVB-T TV

- 1. Choose the menu item "DVB-T TV" in the main menu.
- 2. Press [OK] to enter TV-mode.
- 3. Press [CH+] and [CH-] to switch.
- 4. Press [EXIT] to get back to the last menu item.



DVB-T TV Menu

After entering the DVB-T TV service, press [MENU] button to make the menu appear. By navigating through different options, you can have access to channel list, channel management, automatic channel search function, DVB-T audio settings, channel info, aspect ratio, subtitle function, teletext, AFS setting, and CONAX CA information.



Channel list



To display channel information, preview the program, and to access the Electronic Program Guide (EPG).

Channel management



To rearrange and to edit the TV channel list by skip, move, and delete functions.

Auto search



To search the available channels automatically.



Audio settings



To select either master or secondary language as well as the audio channel of current service

Channel information



Provide the information of current service's system parameters and signal information

Aspect ratio



To adjust image aspect ratio into full-screen, letter-box, and none

Subtitle



To activate or deactivate the subtitle function

Teletext



CONAX CA



To access CONAX CA card menu. In this menu, you can check subscription status, check event status, check token status, change CA PIN, change maturity rating, get Conax CA information and get CA message.



* **AFS** - Auto Frequency Switching is a smart feature that allows the user to watch a channel when moving between 2 cities/areas where the channel is broadcasted in different frequencies. For example, channel "ABC" in city A is broadcasted on frequency 474MHz. In city B, this channel "ABC" is broadcasted on frequency 490MHz. After having scanned in each region once, when moving from city A to city B or vice versa, user can keep watching the channel "ABC" without performing auto search to find the new frequency in city B. When AFS is activated - no matter whether manual or auto mode – while scanning, the tuner recognizes equals channel names. Each channel is only saved on one program place. All frequencies a channel has been found on are saved in an invisible database in the same order as them have been found.



When changing program an info bar is displayed for a few seconds. Besides the program place number, the channel name and antenna strength, the bar also shows the number of available frequencies of the current station (here 4) and the number of the current frequency (here 1). While the info is displayed, the [VOL] or [VOL] buttons can be used to manually switch to the next or previous available frequency. At any time, the FR $rac{1}{2}$ and FF buttons can be used for the same function.

Pagina 11



There are three AFS modes available:

1. **OFF**: AFS function deactivated

2. **Manual**: the user can manually switch between available frequencies of the current channel and manually perform new scans.

3. Auto: when signal is weak for a preset number of seconds, the tuner seeks among the frequencies of the current channel which are available from the database. If none of the available frequencies shows a signal, the tuner automatically performs a new scan.

Note: The information of the AFS database is erased when setting the tuner to factory defaults.





DVB-T Radio

1. Press $[CH\blacktriangle]/[CH\blacktriangledown]$ buttons to select the Ratio item and then press [OK] button to enter the radio mode.



- 2. Press $[CH\blacktriangle]/[CH\blacktriangledown]$ buttons to select your preferred radio channel.
- 3. The radio service will start instantly.





Movie

This section below will explain how to quickly play a video file stored on USB device.

- 1. After selecting movie playback mode on the home screen, file browser screen will appear. Press [OK] button to select the root folder.
- 2. The available video files will appear on screen. Use [CH▲] and [CH▼] buttons to scroll up and down through files, and then select the desired file by pressing [OK] button. The video file will instantly start playing.

NOTE: Users can only choose video files under this mode. System will not support music or photo files under this mode.

3. Press [EXIT] button to return.





NOTE:

- 1. Press the FR / FF button to increase or decrease the playing speed.
- 2. Press the [PLAY/PAUSE] button to pause or resume music playing.
- 3. Press [RED \square] button to delete highlighted file/folder.



Music

The section below will explain how to quickly play a music file stored on USB device.

1. After selecting music playback mode on the home screen, file browser screen will appear. Press [OK] button to select the root folder.



Music

Hans Middlergh

2. The available audio files will appear on screen. Use [CH▲] and [CH▼] buttons to scroll up and down through files, and then select the desired file by pressing the [OK] button. The audio file will instantly start playing.

NOTE: users can only choose music files under this mode. Video or photo files are not supported under this mode



NOTE:

- 1. Press the FR / FF button to increase or decrease the playing speed
- 2. Press the [PLAY/PAUSE] Dutton to pause or resume music playing.
- *3. Press* [*RED*] *button to delete highlighted file/folder.*



Foto

The section below will explain how to view a picture file stored on USB device.

- 1. After selecting photo viewing mode on the home screen, file browser screen will appear. Press [OK] button to select the root folder.
- Available picture and folders will appear on screen. Use [CH▲]/[CH▼]/[VOL▶]/[VOL▲] buttons to browse the folder, and then select the desired one by pressing [OK] button.

Note: users can only choose photo files under this mode. If users choose music or video files, the system will not support.

- A picture preview will appear. Press [CH▲]/[CH▼]/[VOL▶]/[VOL▲] to select a picture, and press [OK] button to display the picture in full screen mode.
- 4. Press [EXIT] button to return.







NOTE: *Press the* [*PLAY/PAUSE*] button to pause or resume photo slideshow.



System settings

This is the menu screen of system settings. Users can adjust the country/language setting, picture quality, monitor port setting, HDMI setting, antenna power output, reset default, and proceed to a software upgrade. Use $[CH\blacktriangle]$ and $[CH\lor]$ buttons to highlight the desired item and press [OK] button to select one.



Country/language



To set up the OSD language and DVB-T regional settings

Display setting



To adjust picture brightness and colour setting (hue, contrast, and saturation)

Monitor-port setting



To set up the video output format through monitor port

HDMI setting



To set up the image type of HDMI output

Antenna power output (+5V)



To provide/stop providing antenna phantom power



Version upgrade



To upgrade the user interface software version via USB*

Reset default



To reset all settings to factory default

* Select "software upgrade" to upgrade the software, select the software on the USB-medium and confirm with [OK] button. The upgrade process should not be interrupted in order to prevent damage. Reset the tuner to factory settings after the software upgrade.





Record function

NOTE: HR-V supports both *DVB-T TV* and *DVB-T Radio* recording.

- During TV or Radio mode, press [REC] to start recording TV/Radio programs. When the unit starts to record, **OREC** icon will appear on the upper left screen & the timer menu (disappear in 10 sec without control) will appear on the lower left screen simultaneously. *NOTE:*
 - a. Please ensure that a USB Storage device is connected to the unit before recording.
 - b. To ensure successful recording on storage device with NTFS system, please plug the storage in Windows operated computer and perform "Safely Remove Hardware" application before using it with HR-V
- 2. Recorded TV programs can be played back in Movie mode. And the recorded Radio programs can be played back in Music mode.

Important notes:

- *i.* A recorded program will be stored in a default folder named "Recorded_Program". The file types will be ".TSV" file for TV program and ".TSA" file for Radio.
- *ii.* The file is named as (Channel Name) + (Recorded Date Recorded Time)
- *iii. Maximum file size of FAT/FAT32 is 4 GB, if the file exceeds this size, the system will cut the recorded file into 2 parts.*
- *iv.* 1 GB storage can record TV program for approximately up to 45 minutes.
- v. Storage files system can support FAT/FAT32/NTFS format.
- vi. Generally all USB 2.0 flash drive can be used as recorded file storage. However, there are cases when the USB flash drive can't store recorded programs from DVB-T receiver unit. It's strongly suggested to format the USB storage device by PC or laptop before it's inserted into the DVB-T receiver unit.
- vii. WARNING! Please do not edit the "*.PLT" & "RECORD.TMP" files. Modifying/deleting this file will cause error on recorded file.



7.3 Reset possibility

Ensure the end user always has the possibility to reset the interface.

This can be done by removing the power connector from the interface and wait 5 minutes, and then put back the power plug to the interface.

or

Place a (interruption) switch to the cable kit on the power cable (red).

Press the switch and wait 5 minutes, and then press it again.

7.4 Last but not least!

Check the following points before installing the interface permanently.

- Check if the picture is fine
- Check if the remote is working
- Check if the DVB-LOGIC shot down when igntion is OFF
- Check if the DVB-T signal is fine via the menu
- Tell the customer how the interface is reset.
- Enter the service manual and let the customer read and sign.
- Make a copy of the following sections of the service manual and put it in your records:
 - *a)* Installation overview
 - b) Location indication products
 - c) Data installer
 - d) Gegevens installateur



8: FAQ

Trouble Shooting Q&A

Most of the troubleshooting issues can be easily resolved. The most common cases and their respective solutions are listed in the table below. If the problem persists, please contact the after sales service.

Problem Possible Reason		Solution	
No nisturo no sudio	The power cord is not properly inserted into the unit.	Check the power wire connection.	
No picture, no audio.	The unit is not switched on.	Press [POWER] button.	
	Unit is in stand-by mode.	Press [POWER] button.	
In DVB-T mode, the number of DVB-T	The number of available channels is limited due to the local broadcasting environment. The available channels can vary depending on the area.	Perform "Auto Search" or "Manual Search" to rescan all the channels.	
channels is not as much as we expected.	The signal quality of some TV channels is too low.	Please use active antennas instead of passive antennas for better reception quality.	
	Some TV channels are not available.	Only the locally free broadcasted channels can be viewed. They can differ depending on the area.	
In DVB-T mode, all of the channels show "no signal" or random mosaic tiles appear on the display.	Some TV channels signal quality is too low.	Please use active antennas instead of passive antennas for better reception quality.	
	The antennas are not properly connected.	Please check the connection of the antennas.	
	No DVB-T service is provided in the area.	Check your country DVB-T coverage map. It is not possible to watch digital TV/listen to digital radio in non-covered areas.	
	Incorrect Regional Setting	Please check whether "Regional Setting" is correct, and perform "Auto Search" to rescan all of the channels.	
In DVB-T mode, no video or audio and	No Smart card is inserted	"Scrambled" message will appears when the TV/Radio signal received is paid-TV. To watch these channels, please insert a valid smart card into CA slot on front panel.	
appears on the screen	Smart card is out of date	Please check your subscription date. If your subscription date is already out-of-date, please contact your service provider to extend your subscription.	
The video is fine but	The audio volume is too low.	Press [VOL▶] button to raise the volume.	
there is no sound.	The audio is muted.	Press [MUTE] button to disable the mute function.	

The remote control does not work	o power.	Check the remote control battery. <i>NOTE: the</i> <i>new remote control might be supplied with a</i> <i>small plastic insulator to avoid discharge of</i>	



	battery power. Check that the plastic insulator
	has been removed.
No "line-of-sight" between unit	Ensure there are no obstacle between the
and controller	controller and the unit.



Pagina 22

9: WARRANTY

The product is designed for automotive use and his environment. The warranty of the product is one year.

No warranty:

- not break the labels attached on the board.
- Damaged of the interface
- Own reperations
- Modified cables

10: TECHNICAL DATA

Operation voltage	10.5 – 14.8V DC	
Stand-by power drain	<1mA	
Operation power drain	<1200mA	
Power consumption	<16,5W	
Temperature range	-30°C to +80°C	
Weight	333g	
Measurements B x H x T	-140 x 30 x 105 mm	€ ===12V DC
AL A 34 L 49 A 19		LA PODIA

11: TECHNICAL SUPPORT

All our products are manufactured under strict quality control. Each device is being tested before shipment. If nevertheless do occur problems or if you have technical questions, contact us directly under:

Distribution by:	NavInc
Technical support email:	info@navinc.nl
Technical support tel:	0031 (0)40 7511912

In addition to constant product update and development related changes the instruction manuals of the devices are constantly edited and kept up to date.

To enable us to provide you with the right information and support for the device you have got at hand please add the following information to every inquiry:

Date of purchase, your name and address, item number and the type of your vehicle.